

Elma Vision 4G PTZ



Model No.: SW-2MP-A-4G

Camera	
Image Sensor:	1/2.8" IMX307 CMOS
Effective Pixels:	1920(H)x1080(V)
Signal System:	PAL/NTSC
Frame Rate	25 fps@1920*1080, 25fps@720*480, 25fps@288*192
Minimum Illumination:	Color: 0.5 Lux @F1.6
	B/W: 0.09 Lux @F1.6
	0 lux with IR
Optical zoom	20x, auto-focus
Focal Length	6-22mm
Field Viewing	81.1°-26.2°
Day & Night:	Auto IR cut filter
Two-way audio	Support
DNR	3D
P2P remote monitor	Support
Anti-shake:	Support
Shutter	Adaptive
Storage	Support for max 128GB micro SD card

Pan & Tilt	
Pan Range:	355°
Pan Speed:	0.01° to 35°/s, 3 level optional
Tilt Range:	0°-90° (Auto Flip)
Tilt Speed:	0.01° to 30°/s, 3 level optional
Number of Preset:	128
Patrol:	5 patrols, up to 16 presets per patrol
Pattern:	4 patterns
IR	
IR Distance	60 meters, 6 sets of IR array LEDs
IR ON/OFF	Auto / Manual
Network	
Image setting	Set by App/Software
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, FTP, 802.1x, QoS, HTTPS, IPv6
Interface protocol	ONVIF, CGI
Network Type	FDD-LTE, TDD-LTE, WCDMA/HSPA+, TD-SCDMA, GSM/GPRS/EDGE
Band	LTE B1/B3/B8/B38/B39/B40/B41
	WCDMA 2100/900MHz, TD-SCDMA B34/B39
	TD-SCDMA B34/B39
	GSM/GPRS/EDGE: 900/ 1800MHz
Rate	FDD-LTE/TDD-LTE: upstream 50M / downstream 150Mbps
	HSPA+: upstream 5.76M / downstream 21Mbps
	TD-SCDMA: upstream 2.2Mbps / downstream 2.8Mbps
USIM/SIM	Micro SIM Card
Access Point	Support
Alarm	Motion detection, shield alarm, full storage
Stream	1080P + VGA + QVGA
General	
Weight	2.5KG
Product Size	22*14*14cm
Packing Size	18.5*19.5*25cm

Mounting Type	Wall mounting / Lift
Input	12V DC, 2A
Power Consumption:	Day: <10W Night: <15W
Working Temp./Humidity:	-10 °C-60°C
	90% or less
Material	Aluminum alloy
Protection Level:	IP66 standard (outdoor dome)