

APPLICATION

“bun THERMOMAX” is a temperature recorder and alarm system with an external sensor for extremely low or high temperatures. It is powered by 2 replaceable AA batteries for up to 6 years and connects directly to Wi-Fi.

More than an accurate meter and a reliable logger, “bun THERMOMAX” is also a cloud-based alarm system.

All setting parameters like measurement intervals, upload intervals, minimum and maximum allowed temperature thresholds can be set through a web-based application on any platform. It sends out email and text message alarms as soon as temperature exceeds or falls below pre-set limits. It also provides access to the records history, graphs and periodical reports. Its hardware and software installation is very easy and does not require any specific tools or applications.



Its hardware and software installation is very easy and does not require any specific tools or applications.

GENERAL SPECIFICATIONS

Sensor	External temperature sensor	
Temperature measurement and alarm range (Sensor only)*	°C	-200 to +175 (up to +850 by order)
	°F	-325 to + 350 (up to +1560 by order)
Upload temperature range (device)	°C	-5 to +70
	°F	20 to +160
Temperature measurement Accuracy	°C	Max ± 0.8 °C (± 1.44 °F) - Depending on range
Power supply	2 x AA replaceable batteries	
Sensor's protection class	IP 67	
Compliances	IEEE 802.3, EN 61326-1, EN 61010, EN 12830, FCCID: 2AHMR-ESP12F, CE, ROHS, HACCP	
Battery life*	Up to 6 years	
Upload intervals	One hour to once a week (or on demand)	
Record intervals	1 minute to 120 minutes (down 5 sec. by order)	
Interface	Wi-Fi - IEEE 802.3 – 2.4 GHz	
Max. number of internal records	16,384 – Automatic cloud sync and replace	

*Temperature measurement will be less accurate in sensors with wider temperature range. To achieve highest accuracy narrower temperature range is recommended. “Bun THERMOMAX” can drive 2,3,4 wire RTD sensors. PT type, range and accuracy (Class Y [1/3 B], Class A, Class B) can vary based on order and calibration. By default,

“Bun *THERMOMAX*” has a Y Class PT1000 sensor in a stainless-steel pocket with a 1.5 meter length cable. The cable includes 2 silver coating wires with PTFE cover and Fiberglass sleeving.

*Depends on reading and upload intervals and environmental conditions. Battery life is more than 6 years in a standard set up. (Standard set up is room temperature 20°C measurement every 15 minutes upload every 48 hours).

AMBIENT CONDITIONS

Storage temperature	°C	-25 to +75
---------------------	----	------------

DIMENSIONS

Diameter (max.)	L	mm	80.0
Height (max.)	H	mm	34.5

Loggerflex smart devices Ltd.



Loggerflex smart devices Ltd.

2-3304, Cambie St.
Vancouver, BC
V5Z 2W5
Canada

info@Loggerflex.com
www.loggerflex.com

Tel.: (604) 210 22 42
Toll free: +1 888 365 88 80



Made in Canada